

PF-2S Step Speed Head 3HP

Feature

- ◆ 9" x 42" Table standard
- ◆ 9" x 49" Table optional
- ◆ 16 speeds (80~5440 r.p.m) optional
- ◆ X. Y. Z - axes Dovetail slide way
- ◆ X. Y - axes Coated with Turcite -B
- ◆ X. Y. Z - axes Hardened & ground
- ◆ Quill and spindle are chrome moly-bdenum steel, hardened and ground.
- ◆ Meehanite casting on machine column.

Standard Accessories

Draw Bar	1 set
Tools	1 set
Toolbox	1 set
Plastic Splash Guard	1 set
One Shot Lubrication	1 set

Optional Equipment

- ◆ Coolant System
- ◆ Chip (pan) Guard
- ◆ Work Lamp
- ◆ Milling Chuck with Collets
- ◆ Clamping Kits (CK-104) 52 Pcs
- ◆ 6" Angle Machine Vise
- ◆ Precision Ball Screw for X.Y-axes
- ◆ Digital Readout for X.Y.Z-axes
- ◆ Air Power Draw Bar

**PF-2VS**

Variable Speed Head 3 HP



PF-6H

Inverter Speed Head
Step Speed Head 5HP

Feature

5HP High - Torque Inverter Head (7.5HP Optional)
Lead screw double nut desing easey adjusting Backlash

- ◆ 10" x 50" Table Standard
- ◆ 10" x 54" Table Optional
- ◆ Spindle Taper NST#30 or R8.NST#40
- ◆ X - axis Dovetail slide way
- ◆ Y, Z - axes Square Ways
- ◆ X, Y - axes Coated with Turcite - B
- ◆ X, Y, Z - axes Hardened & ground
- ◆ Quill and spindle are chrome moly-bdenum steel, hardened and ground.
- ◆ Meehanite casting on machine column.

Optional Equipment

- ◆ Coolant System
- ◆ Adjust Chip (pan) Guard
- ◆ Adjustable Safety Table Cove
- ◆ Work Lamp
- ◆ X.Y.Z-axes Power Feed
- ◆ Milling Chuck with Collets
- ◆ Clamping Kits (CK-104) 52 Pcs
- ◆ Angle Machine Vise
- ◆ Air Power Draw Bar

Standard Accessories

Draw Bar	1 set
Tools	1 set
Toolbox	1 set
Plastic Splash Guard	1 set
Auto Lubrication	1 set

