



佳杰國際有限公司  
WTB INTERNATIONAL CO., LTD.

食品機械系列  
FOOD MACHINE SERIES

# 食品攪拌機

FOOD MIXER  
MÁQUINA MEZCLADORA  
KÜCHENMASCHINE  
MÉLANGEUR DE NOURRITURE

- 膠帶座
- 封盒 杯機 (3機種)
- 魔帶結束機 (5機種)
- 食品攪拌機 (24機種)
- 保鮮膜包裝機 (2機種)
- 蔬果膠帶束口機 (2機種)
- TAPE DISPENSER
- BOX • CUP SEALER (3 models)
- TWISTING TIE MACHINE (5 models)
- FOOD MIXER (24 models)
- FILM PACKAGING MACHINE (2 models)
- VEG. & FRUIT TYING MACHINE (2 models)



包裝機械系列  
PACKAGING MACHINE SERIES

# 連續式封口機

CONTINUOUS SEALING MACHINE  
SELLADORA EN LÍNEA  
UNUNTERBROCHENE DICHTUNG MASCHINE  
MACHINE CONTINUE DE CACHETAGE

- 連續式封口機 (24機種)
- 手壓 腳踏式封口機 (15機種)
- 自動計重 計量充填機 (7機種)
- 自動計量 計重充填包裝機 (8機種)
- 真空包裝機 (8機種)
- L型自動包裝機
- CONTINUOUS SEALING MACHINE (24 models)
- HAND TYPE • FOOT TYPE SEALER (15 models)
- AUTO. WEIGHING FILLING MACHINE (7 models)
- AUTO. WEIGHING FILLING PACKING MACHINE (8 models)
- VACUUM SEALING MACHINE (8 models)
- L TYPE AUTOMATIC SEALING MACHINE



# WTTB<sup>®</sup> PACKAGING MACHINE SERIES 佳杰包装机械系列



機械代號說明： MACHINE CODE ILLUSTRATION：

WA-

- A: Adjustable speed 可調速
  - B: Caster with brake 剎車輪
  - C: Counter 計數器
  - P: Printer 印字器
  - S: Stainless steel 不銹鋼
  - T: Trimmer 修邊器
  - U: Compression unit 壓風裝置
  - W: Weighing 計重
  - Q: Quantative 計量
- Machine No. 機號



CE  
**WA-621P**

小型臥式連續封口機  
LIGHT DUTY HORIZONTAL  
SEALING MACHINE 專利號碼 PATENT NO-86144



CE  
**WA-622S**

小型立式連續封口機  
LIGHT DUTY VERTICAL  
SEALING MACHINE 專利號碼 PATENT NO-85591



CE  
**WA-624**

小型臥式雙邊連續封口機  
LIGHT DUTY HORIZONTAL DOUBLE  
SIDES SEALING MACHINE 專利號碼 PATENT NO-45155



**WA-721**

臥式連續封口機  
HORIZONTAL SEALING  
MACHINE 專利號碼 PATENT NO-114403



CE  
**WA-627**

重型連續封口機 HEAVY DUTY CONTINUOUS  
SEALING MACHINE 專利號碼 PATENT NO-85591



CE  
**WA-722**

臥式連續封口機 (附印字器)  
HORIZONTAL SEALING MACHINE  
(ATTACHED WITH PRINTER) 專利號碼 PATENT NO-114403



CE  
**WA-724P**

中型臥式雙邊封口機  
DOUBLE SIDES SEALING MACHINE



CE

**WA-727**

立式連續封口機 (附印字器)  
VERTICAL SEALING MACHINE  
(ATTACHED WITH PRINTER)



**WA-1000W/1000Q/1000S**

電腦自動計重 / 計量充填機  
COMPUTER AUTO. WEIGHING /  
QUANTATIVE FILLING MACHINE



CE

**WA-729P**

真空吸氣封口機  
VACUUM TYPE  
SEALING MACHINE 專利號碼 PATENT NO-15114



**WA-306/307**

液體自動計量充填包裝機  
AUTOMATIC FILLING & PACKING  
MACHINE FOR LIQUID



冬瓜茶、奶茶  
紅茶、牛奶...  
等專用包裝機



**WA-308/309**

液體自動計量充填包裝機  
AUTOMATIC FILLING & PACKING  
MACHINE FOR LIQUID

**WA-304 /305**



**WA-314**

粉粒體自動計量充填包裝機  
AUTOMATIC FILLING & PACKING  
MACHINE FOR POWDER OR GRIT

# WA-7206

## 立式封口機 VERTICAL SEALING MACHINE

- 本機特性與WA-622 類似，但機體結構較強大，可支撐中型包裝物。
- 附活動輪，機械移動方便。
- 全齒輪式傳動，運轉穩定加長零件壽命，封口優美。
- 多重安全防護措施。
- 適合包裝袋高 10-40公分之各種五金、液體、粉粒體、糊狀、油性物質之封口。
- 本機型有不鏽鋼及板金機身可供選購。
- A heavier model than WA-622 with similar features.
- Equipped with four castors for easy mobility.
- Fully gear drive assures long service life and superior sealing quality.
- Comprehensive safety guards.
- Ideal for sealing liquid, powder, glue hardware kits and oily products. Bag length range from 10 to 40 cm.
- Stainless steel machine frame is available.



# WA-7212

## 生產線型臥式封口機 PRODUCTIVE TYPE SEALING MACHINE



- 此機是生產線輸送帶與封口機兩機一體高效率機種。
- 本機配置自動入料輸送台，大幅提昇封口產能。適合五金、零件組裝生產線之封口。
- 可同時 8 人作業。
- 輸送台最大載重 150 公斤。
- 視工作速度，輸送速度可無段調整。
- 輸送台離地高度 800mm。
- 多重安全防護措施。
- 雙邊設有不鏽鋼或木質之工作台，工作台下方設腳踏板，便於工作者坐著使用。
- 封口完成後，設有成品儲存槽。
- 此機是三相 220V 電壓控制系統。
- A sealing machine fitted with the conveyor for efficient operations. Ideal for mass production line.
- Equipped with infeed conveyor for greatly upgrading productivity. Suitable for mass production for hardware and part assembly.
- Permits for 8 operators to work at both sides.
- Maximum loading capacity on conveyor is 150 kgs.
- Variable conveyor speed.
- The height of the conveyor from floor is 800mm.
- Comprehensive safety guards.
- Stainless or wood tables on both sides. Foot stands under table allow operators to sit for working.
- Equipped with product storing channel.
- 3 phase, 220V power system.



皮帶式壓風裝置，在封口前將袋內空氣壓出。

**Belt type:** Employs belts to force air out of bags before sealing



修邊器裝置封口後，將包裝袋殘餘邊切除。

Employs two blades to trim package after sealing for neat edge.



充氣裝置，將袋內充氣，有效緩衝防止包裝物受損。

To blow air into the bags for preventing package from crashing.



抽風裝置，可將袋內空氣抽掉80%減少成品體積，並延長產品壽命。

To evacuate air out of bag.



擠壓式壓風裝置，具強勁壓風效果。特別適合膨鬆之柔軟物封口等。

**Hydraulic type:** Provides a powerful compression effect. Recommended for expanded products, such as sponge ...etc.



印字器適合印製造或有效日期、批號、重量...等。

Printing dates, lot no and weight... etc.



活動輪提供機械移動之方便性。

Castors provide easy mobility of the machine.

## 標準附件：

- 保險絲。
- 封口帶(可選擇不鏽鋼帶或鐵氟龍帶)。
- 工具箱及工具乙組。
- 有印字配備另加油墨輪、鋁合金字盒(可選備銅字或鋼字)。
- 說明書。

## STANDARD ACCESSORIES

- **FUSE**
- **SEALING BAND**  
(Choice of stainless steel or teflon band)
- **TOOL BOX AND TOOLS**
- **INK ROLLER AND ALUMINUM ALLOY WORD BOX.**  
Choice of bronze or steel words. Supplied only for models equipped with date coder.
- **OPERATION MANUAL**

## 選購附件：

### ●計數器

1. 機械 4 碼式：顯示已封口成品數量。
2. 警報型：採 LED 數字顯示單批數量，設定數量到達時有警報告知。
3. 雙顯示型計數器：採 LED 數字顯示總數量及單批數量，並於設定數量到達時會發出警報告知。

### ●印字器：

於封口後打印製造日期及保存期限、批號、重量...等。(可選擇銅字、鋼字或鋁合金字)可特訂以外的字、商標等，標準一次可印 28 個字。

### ●輸送台電動昇降：

只適用於立式封口機，採馬達驅動，行程上下極限控制，方便快速調整輸送架之高低，省時省力。

### ●修邊器：

將封口完後之殘餘邊切除，以利美觀另附壹組預備用刀片。

### ●水冷式冷卻系統：

具最快速之特殊冷卻效果。可使特殊材質之包裝袋封口線更美麗牢固。

### ●壓風裝置：

可選擇皮帶式或擠壓式裝置，將包裝袋內空氣排出。可用於海綿體、柔軟物及手套壓風包裝，以節省包裝空間。

### ●反向送料：

可指定反向送料(由右而左)。

### ●充氣裝置：

將袋內充氣，有效緩衝防止包裝物受損及增加其美感。

### ●方管腳架：

附四個活動輪(適用WA-6XX系列機種)下方並附隱藏式工具箱。

### ●真空吸氣裝置：

附真空抽氣泵浦，將包裝袋內空氣吸出，以節省包裝空間及延長食品保存期限。

## OPTIONAL ACCESSORIES

### ●COUNTER:

1. Mechanical 4-digit type:  
For indicating the sealed products.
2. Alarm type:  
LED displays the single lot number. Once quantity reaches, alarm sounds.
3. Double display counter:  
LED displays the total quantity and single lot number. Once quantity reaches, alarm sounds.

### ●DATE CODER:

For printing the manufacturing date, storage duration, lot number and weight etc. Standard printing capacity 28 words. (Double lines printing)  
(Choice of bronze, steel, or aluminum words)  
Custom words and logo are available.

### ●POWER TABLE RAISING:

Available only for vertical sealers.  
Motor drive with limit switch control for entire stroke.  
Provides effortless and convenient elevation of conveyor table.

### ●TRIMMERS

Designed to trim the bag edge after sealing. Furnished with one set spared blade.

### ●WATER COOLING SYSTEM:

Provides fast cooling effect and ensures secure sealing line.

### ●BAG COMPRESSION UNIT:

Choice of belt or squeeze type. It forces out the air in the bag. Excellent for packages such as sponge, soft products and gloves for saving package volume.

### ●DIRECTION OF FEED:

A reversible feed is available. (Feed from right to left)

### ●AIR BLOW ATTACHMENT:

For filling air into bags to prevent package crushing and upgrade visual effect.

### ●TUBULAR LEGS:

Fitted with 4 castors and built-in tool cabinet. Available for WA-6XX series only.

### ●VACUUM SUCTION DEVICE:

With vacuum suction pump for sucking air out of bags. It saves package volume and extends expiry date.

# HAND TYPE IMPULSE SEALER 瞬熱

## 手壓式封口機



CE WA-300H



CE WA-300HC



CE WA-100H

### FEATURES:

- Compact construction.
- Light weight for comfortable operation.
- Minimum trouble.
- Electronically controlled impulse sealing gives time saving and safety guard.

### APPLICATIONS:

Designed for sealing various bag materials such as PE, PP, PVC etc.

Ideal for users of shops, stores, home, and wholesale distributors.

### 特性：

- 結構輕巧。
- 重量輕，操作輕鬆。
- 故障率極低。
- 電子式控制，省時，安全性佳。

### 用途：

適合各種袋材質，如 PE, PP, PVC 等。

適合商店、超商、家庭、配銷處。

# FOOT TYPE DIRECT HEAT SEALER 直熱

## 腳踏式封口機



CE WA-300DF

### FEATURES:

- Foot operated for maximum operation convenience.
- Optional date coder allows for sealing and date coding at a time.
- Direct heating gives dependable and secure sealing result.
- Stand can be dismantled into two sections for reducing packing volume, and saving freight.

### APPLICATIONS:

Designed for sealing poly bags, Polycello, PE, PP film coated with aluminum foil, Tin foil, copper foil; OPP, OPS, PSP, glued paper etc.

Ideal for users of shops, stores, wholesale distributors etc.

### 特性：

- 腳踏式操作，操作方便。
- 配合印字器（選購配備），可同時作封口及印字作業。
- 直接加熱，封口性能牢固、可靠。
- 腳架可拆卸成兩段，減小包裝體積，減少運費。

### 用途：

適合積層袋材質；如玻璃紙, PE, PP, 鋁箔、錫箔、銅箔 OPP, OPS, PSP, 貼合紙等。

適合商店、超商、配銷處。

# FOOT TYPE IMPULSE SEALER 瞬熱

## 腳踏式封口機



CE WA-450F



WA-300H N/P

### FEATURES:

- Foot operated for maximum operation convenience.
- Optional date coder allows for sealing and date coding at a time.
- Electronically controlled impulse sealing gives great time saving and safety guard.
- Stand can be dismantled into two sections for reducing packing volume, and saving freight.
- Automatic and continuous sealing with switch for foot control. (HN Series)

### APPLICATIONS:

Designed for sealing various bag materials such as PE, PP, PVC etc.

Ideal for users of shops, stores, wholesale distributors.

### 特性：

- 腳踏式操作，操作方便。
- 配合印字器（選購配備），可同時作封口及印字作業。
- 電子式控制、省時、安全性佳。
- 腳架可拆卸成兩截，減小包裝體積，降低運費。
- 可連續自動封裝並附腳踏開關（HN系列）。

### 用途：

適合各種袋材質：如 PE, PP, PVC 等。  
適合商店、超商、配銷處。

MODEL	Source (V)	Impulse Power (W)	Max. Sealing Length (m/m)	Heat Time (Sec.)	Max. Sealing Thickness (m/m)	PCS/CTN	Packing Dimensions (cm)	Weight (N.W./G.W.) (Kg)
WA-100H	110/220	160	100	0.2-1.3	SINGLE SIDE 0.2mm	12	50 x 35 x 40	20/22
WA-200H		260	200			10	55 x 35 x 40	21/23
WA-300H		380	300			8	50 x 50 x 40	28/30
WA-400H		600	400			6	60 x 40 x 45	30/32
WA-200HC		260	200			6	35 x 45 x 50	24/27
WA-300HC		380	300			4	55 x 25 x 50	19/21

MODEL	Source (V)	Impulse Power (W)	Max. Sealing Length (m/m)	Heat Temp. (°C)	Max. Sealing Thickness (m/m)	Packing Dimension (cm)	Gross Weight (Kg)
WA-210DF	110/220	250	210	50-300	1	75 x 40 x 35	22
WA-250DF		300	250				23
WA-300DF		350	300				24

MODEL	Source (V)	Impulse Power (W)	Max. Sealing Length (m/m)	Heat Time (Sec.)	Max. Sealing Thickness (m/m)	Packing Dimensions (cm)	Gross Weight (Kg)
WA-300F	110/220	400	300	0.2-3	0.4	75 x 45 x 25	23
WA-450F		600	450				28
WA-600F		800	600			90 x 45 x 30	34
WA-300HN		400	300			60 x 45 x 30	22
WA-450HN		600	450				23
WA-600HN		800	600			75 x 45 x 30	26

# 機械規格 SPECIFICATIONS

型式	WA-621(P)	WA-622(P)	WA-624(P)	WA-625(P)	WA-626(P)	WA-627(P)	WA-721	WA-722	WA-724(P)	WA-7206(P)	WA-727	WA-729(P)	WA-7212
輸送台最大載重(kg) Max. conveyor belt load (kg)	10	10	10	10	10	100	—	20	20	15	20	20	100
鋼帶尺寸(寬×長)(cm) Steel band size (W x L) (cm)	1.5 x 75	1.5 x 75	1.5 x 75	1.5 x 75	1.5 x 100	1.5 x 75	1 x 75	1 x 108	1 x 108	1.5 x 75	1 x 130	1 x 125	1 x 108
輸送帶尺寸(寬×長)(cm) Conveyor belt size (W x L) (cm)	13 x 155(186)	13 x 155(186)	13 x 155(186)	13 x 155(186)	13 x 168(199)	30 x 410	—	20 x 225	20 x 225	18 x 155(168)	20 x 270	20 x 225	30 x 820
尼龍帶尺寸(寬×長)(cm) Nylon band (W x L) (cm)	0.5 x 42.5(100)	0.5 x 42.5(100)	0.5 x 42.5(100)	0.5 x 42.5(100)	0.5 x 42.5(100)	0.5 x 42.5(100)	—	0.5 x 125	0.5 x 69(25)	0.5 x 42.5(100)	5 x 125	0.5 x 69(25)	0.5 x 69(25)
送袋速度(M/min) Conveyor speed (M/min)	0-12	0-12	0-12	0-12	0-12	0-10	0-10	10	10	0-12	10	0-10	0-10
輸送台傾斜 Conveyor table tilts	—	—	—	—	可選擇 available	—	—	0~30°	—	—	—	0~30°	—
電壓(V) Electricity (v)	110/220/1PH	110/220/1PH	110/220/1PH	110/220/1PH	110/220/1PH	220V/3PH	110/220/1PH	110/220/1PH	110/220/1PH	110/220/1PH	110/220/1PH	110/220/1PH	220V, 3PH
使用功率(W) Power (w)	520(620)	520(620)	1020(1220)	1020(1220)	870(970)	1270(1370)	480	1050	1650(1850)	520(620)	1050	1600(1700)	2300(2500)
馬達 Motor (1ph.)	50W	50W	50W+50W	50W+50W	100W	50W + 1HP	15W	1/4 HP	1/4 HP	50W	1/4 HP	90W	1 HP
輸送台高度調整範圍(cm)	0-3	10-30	0-3	10-30	0-3	50-100	—	0-7	0-7	10-40	10-60	0-7	—
加熱溫度範圍 Heating temp range (c.c)	0-399	0-399	0-399	0-399	0-399	0-399	0-399	0-399	0-399	0-399	0-399	0-399	0-399
淨重/毛重(kg) N. W./G.W (kg)	30/32	32/34	50/60	60/70	40/42	150/200	5/6	100/110	150/200	60/70	150/210	100/140	300/400
機械尺寸(長×寬×高)(cm) Machine dimensions (cm)	80(100) x 40 x 30	80(100) x 30 x 45-80(100) x 75 x 40	80 x 60 x 45(110)	80 x 60 x 45(110)	93(123) x 40 x 30	300 x 60 x 170	50 x 10 x 15	130 x 55 x 100	130 x 90 x 100	80(110) x 50 x 90	170 x 55 x 170	130 x 70 x 100	400 x 100 x 110
裝箱尺寸(長×寬×高)(cm) Packing dimensions (cm)	85(115) x 47 x 35	85(115) x 47 x 35	90(120) x 85 x 50	90(120) x 85 x 50	98(128) x 46 x 35	310 x 70 x 180	55 x 15 x 20	140 x 60 x 110	140x 100 x 110	90(120) x 60 x 100	180 x 65 x 180	140 x 80 x 110	410 x 110 x 120

\* 規格尺寸更改不另行通知

\* 特殊機械規格可另行指定

\* 每包重量要視其比重而定

\* 型號上有 (P) 者，表示加裝印字器 (選購)

\* ( ) 括號內之數據為加裝印字器之規格

\* All specifications and design characteristics shown in this catalogue

are subject to change without notice.

\* Custom specifications are available to meet specific requirements.

\* Bag capacity varies with product specific weight.

\* Suffix (P) represents model with date coder (optional).

\* ( ) represents machine length with date coder.



# WTB<sup>®</sup> FOOD MACHINE SERIES 佳杰食品機械系列

機械代號說明 : MACHINE CODE ILLUSTRATION :

WB-□ □ □

- D: Digital Electronic Display 電子數字顯示
- A: Automatic Bowl Removal 攪拌桶自動進退
- B: Belt Drived 皮帶傳動
- G: Gear Drived 齒輪傳動
- M: Mixing Performance 混合攪拌
- Bowl Capacity (Liter) 攪拌桶容量 (公升)



**WB-10G/20G**

食品攪拌機 FOOD MIXER



**WB-10BD/20BD/30BD/40BD**

食品攪拌機 FOOD MIXER



**WB-30G**

食品攪拌機 FOOD MIXER



**WB-80B/90B/140B**

食品攪拌機 FOOD MIXER



**WB-70B/90B/200B/260B**

食品攪拌機 FOOD MIXER



**WB-260A/300A/380A/500A**

食品攪拌機 FOOD MIXER



**WB-100M/200M**

直立式混合攪拌機  
VERTICAL TYPE MIXER



**WB-110**

保鮮膜包裝機 FILM PACKAGING MACHINE



**WB-210**

魔帶結束機  
 TWISTING TIE MACHINE



**WB-120**

蔬果膠帶束口機  
 VEGETABLE AND FRUIT TYING MACHINE



**WB-888**

桌上型盒・杯封口機  
 BENCH BOX • CUP SEALER



**WB-121**

塑膠袋束口機 PLASTIC TYING MACHINE



**WB-125**

膠帶貼合器 TAPE DISPENSER



**WB-999**

桌上型封盒機 BENCH BOX SEALER



### WB-311FH

收縮包裝機 SHRINKING MACHINE



### WB-350

真空包裝機 VACUUM SEALING MACHINE

## BOX SEALER



### WB-777 封盒機

#### USAGE:

- To WEO, OPS, OPP, PSP, PVC, EPS food packing cases for shops, stores, houses, mills.

#### FEATURES:

- Light weight
- Easy to operate
- Regulatable high or low temperature to any thickness.
- Direct heat weld, solid and firm.

MODEL	Source (V)	Power (W)	Heat Temp. (°C)	Packing Dimension (cm) PCS/CTN	Weight(kg) N.W./G.W.
WB-777	100/240	14.5	LO: 180, HI: 210	68X26X25/25	10/12



**佳杰國際有限公司**

**WTB INTERNATIONAL CO., LTD.**

台北市110信義路五段5號3B33室  
台北世界貿易中心展覽大樓

**Taipei World Trade Center Exhibition Hall**

Room 3B33, 5 Hsin-yi Road, Sec. 5, Taipei 110, Taiwan.

Tel : 886-2-8788-1451 . 8788-1608

Fax : 886-2-8788-1452

E-mail : wtb.rita@msa.hinet.net

Web site : [www.wtb.com.tw](http://www.wtb.com.tw)