

The Advanced Networking Technology

REPOTEC CO., LTD. http://www.repotec.com TEL: 886-2-8227-1888 FAX: 886-2-8227-1818



>> RP-NA2300

Network Storage Gigabit IDE NAS with USB

This is a high-speed, economical, powerful NAS (Network Attached Storage), especially suitable for small business, SOHO (Small Office or Home Office) or personal data sharing requirement. The device supports Gigabit high-speed transmitting rate and EXT3 file format to make efficient data sharing. It also provides a multiple data sharing way with supporting FTP and WEB server and allows users in a LAN to easily backup data or share files through intranet/internet. With Unicode supported, the device is compatible to multilingual file name. Along with the embedded two USB ports that give a convenient connection for printer and USB storage usage, the SOHO NAS leads you to an unobstructed network.

Feature

- Web-based UI for easy configuration
- Support EXT3 internal H.D file format
- Support FAT16, FAT32, EXT3 USB Storage file format
- Auto Networking Configuration Utility for Windows OS
- Provides Web Server to create a personal web site easily
- Built-in FTP server for user conveniently transfer files by using FTP client
- Supports CIFS/SMB for Microsoft Network remote users easily retrieve files by using "My Neighborhood"
- Supports all standard ATA133 3.5" IDE HD up to 400GB
- Auto-detect HD for new installed HD (Existed Folder and File)
- Provides HD formatting function for new HD or USB storage
- Provides Password security for Web management & HD Access
- · Supports Unicode for different language character
- Compatible Windows 95 /98 /98SE /ME /XP /2000 /NT4.0

Specification

Specification	
Support Protocol	TCP/IP, HTTP, SMB, FTP, EXT3,DHCP, uPnP
Interface	 One 10/100/1000Mbps RJ-45 Ethernet port
	• 2* USB 1.1/2.0 ports
	One Factory Default Setting Button
	One Power On/Off Switch Button
Ethernet Connection speed	• 10/1001000 Mbps
USB Connection speed	• Max. 480 Mbps
Support Hard Diskette	One removable 3.5" external HD (ATA133) up to 400GB
Diagnostic LEDs	Power/Status (Green)
	LAN: 1000M Link/Act (Green), 10/100M Link/Act (Amber)
	HDD: data transfer (Yellow)
	USB: Link/ACT (Green)
Power Supply	External power Adapter DC 12V, 3A
Operating Temperature	Operating Temperature: 0°C~40°C
	Storage Temperature: -10°C~65°C
Dimension	• 220*132*60 mm
Certification	• FCC, CE