

# 油壓立式拉床（外徑拉削）

## Hydraulic Vertical Broaching Machines (External Broach)

### ☆TH-600X235

#### Specifications:

01.引拔力	Broaching Power	3 噸(ton)
02.最大行程	Max. Stroke	600m/m
03.拉刀最大長度	Max. Broach Length	600m/m
04.切削速度	Cutting Speed	1- 6 m/min
05.回程速度	Return Speed	1- 7 m/min
06.主機馬達	Driving Motor	5H4P
07.切削油馬達	Cutting Oil Motor	1/8H 4P
08.潤滑油馬達	Lubricant Motor	
09.最大加工物寬度	Maximum width of processing piece	235mm
10.機械最高尺寸	Highest Dimension of Machine	1980mm
11.機械面積	Area of Machine	1200X1600mm
12.機械總重量	Total Weight of Machine	1300kg
13.工作台高度	Table Height	775mm



#### 特性:

1. 均一的高精度效能
2. 省時及省力
3. 操作簡易、提高工作產能
4. 加工模具簡易，維修方便
5. 適用對象：國內外專業研發汽機車、腳踏車及手工具的製造商

#### Characteristic:

1. Consistent high-accuracy performance
2. Saves time and manpower.
3. Easy to operate with high productivity.
4. Simple processing mold and easy to maintain.
5. Applications: Auto, Motorcycles, bicycles and tools. Processing and manufacturing.

**TH 璨鑫工業股份有限公司**  
TSAN HSIN IND. CO., LTD.

台中市 41144 太平區永平路二段 326 號

TEL:886-4-22755811 FAX:886-4-22700800

E-mail: tsanhsin@tsan-hsin.com.tw