


ROBO-8210VG2AR

Intel® Core™ i7/i5 processor based PICMG 1.3 SHB with DDR3 SDRAM, DVI-I, Dual Gigabit Ethernet, Audio and USB



FEATURES

- Support Intel® i7-620M/i5-520M/P4500 processors in rPGA988 package
- Delivers up to 8GB maximum DDR3 1066/800 on two DIMM sockets
- Support dual display by DVI-I port on bracket
- Support iAMT 6.0 and external TPM via TPM module
- High speed dual Gigabit Ethernet based on PCI Express x1, high bandwidth I/O interface
- Rich I/O connections such as FDD, two Gigabit Ethernet, serial ports, parallel port, USB 2.0
- Four on-board SATA ports support RAID 0,1,5,10

ORDERING GUIDE

Standard	ROBO-8210VG2AR PICMG 1.3(PCI-E+PCI).Intel Core i7/i5 PGA type processors.SHB.w/DVI-I/Dual GbE/Audio/USB
Optional	PA-M1AU Multimedia kit with audio and USB ports PS/2 Keyboard/Mouse Cable with Bracket PS/2 keyboard/mouse connectors on bracket USB cable with bracket Two USB ports with bracket

* Specifications are subject to change without notice.

* Celeron®, Pentium® III, Pentium® 4 and Xeon™ are registered trademarks of Intel® Corporation

* Other trademarks, logo, brands and company names are the property of their respective owners

GENERAL

Processor	CPU & Package: Intel® Core™ i7-620M/i5-520M/P4500 processor in rPGA989 socket
Chipset/Core Logic	Intel® QM57
System Memory	Up to 8GB DDR3 1066/800 SDRAM on two 240-pin DIMM sockets
BIOS	AMI EFI BIOS
Storage Devices	EIDE: N/A SATA: Support six SATA 300 drives (dual SATA ports via backplane) (RAID 0,1,5,10)
Solid State Disk	One Mini-PCIe socket
Watchdog Timer	Programmable via software from 0.5 sec. to 254.5 sec.
Expansion Interface	One PCIe x 16, Two PCIe x 8, Four PCI devices
Hardware Monitoring	System monitor (fan, temperature, voltage)
Power Requirement	N/A
Dimension	Dimension: 338.5(L) x 126.39(W) / 13.33"(L) x 4.98" (W) PCB: 8-layer
Environment	Operating Temperature: 0 to 55°C Storage Temperature: -20 to 80°C Relative Humidity: 5% to 90%, non-condensing
MTBF	N/A

I/O

MIO	Two serial (RS-232x1, selectable RS-232/422/485 x1), one parallel and one FDD channel
IrDA	N/A
Ethernet	-Dual 10BASE-T/100BASE-TX/1000BASE-T Ethernet -PCI Express x1 interface based Gigabit Ethernet -Dual RJ-45 connector with two LED indicators
Audio	HAD interface, 5.1-channel Audio (Realtek ALC 662)
USB	Twelve USB 2.0 ports (Four USB ports via backplane)
Keyboard & Mouse	Two USB 2.0 ports on bracket dedicated to keyboard & mouse

DISPLAY

Graphic Controller	- Intel® Core™ i7/i5 processors integrated Gen 5.75 graphic engine - Provided improved 3D multimedia capabilities including Microsoft DirectX 10, Shader Model 4.0, MPEG-2 and OpenGL 2.1
Graphic Memory	Intel® Dynamic Video Memory Technology (DVMT) 5.0 shares system memory up to 1GB
Display Interface	Analog CRT: up to 2048 x 1536 @ 75Hz DVI-D: up to 1920 x 1200 @ 60Hz

American Portwell

Fremont CA Tel: +1-510-403-3399
Norcross GA Tel: +1-678-969-9808
E-mail: info@portwell.com
http://www.portwell.com

Portwell Japan, Inc.

Tokyo Tel: +81-3-5298-8071
Osaka Tel: +81-6-4807-7721
E-mail: info@portwell.co.jp
http://www.portwell.co.jp

Beijing Portwell

Beijing Tel: +86-10-82701616
Shanghai Tel: +86-21-3222-0505
Shenzhen Tel: +86-755-8621-7695
E-mail: info@portwell.com.cn
http://www.portwell.com.cn

Portwell-Laxsons

India
Tel: +91-22-2685-9911
E-mail: info@portwellaxsons.com

European Portwell

Tel: +31-252-620790
E-mail: info@portwell.nl
http://www.portwell.nl

Portwell (UK) Ltd.

Tel: +44(0)1235-750760
E-mail: info@portwell.co.uk
http://www.portwell.co.uk



Portwell, Inc. (Headquarters)

No. 242, Bo-Ai St., Shu-Lin City,
Taipei County 238, Taiwan
Tel: +886-2-77318888
Fax: +886-2-77319888
E-mail: info@portwell.com.tw
http://www.portwell.com.tw