

7. EASY TO MASTER

Any novice can be trained to be a skilled soldering hand in just one or two hours.

8. SPEEDING UP PRODUCTIVITY

The SY-003 allows direct soldering without pre-soldering. Use of the SY-003 has been proved to boost operational efficiency by 30% to 50%.

9. EASY TO CHANGE TIPS

The solder wire, heater and solder iron tip are available in all standard sizes. Customer's iron tips available on request.

10. SIMPLE STRUCTURE AND HIGHLY EFFICIENT FUNCTIONS

The SY-003 eliminates the need for time-consuming soldering jobs.

7. 易學，新手之利器

新手只要經1至2小時的訓練即可成為熟練優良的焊接高手。

8. 提高產量

採直接焊接，不必鍍錫預焊或外加助焊劑，節省作業動作，提昇工作效率及產量，降低生產成本。

9. 耗品補充，更新容易

所使用之錫絲、烙鐵及烙鐵頭係屬國際標準規格補充容易，不需任何特殊工具及技巧即可更新。

10. 完整的焊接技術轉移

本公司擁有一流的焊接技術工程師及完整的焊接技術轉移計畫，可將高超的焊接技巧完完整整轉移至使用者身上。

SPECIFICATIONS

1. Power: 110/220/240 V AC., 50/60 Hz, as requested.
2. Usable solder wire diameter:
Standard 0.8mm - 1.2mm (0.03 - 0.05 inches)
3. Adjustable solder feeding length:
0-30mm (0-1.2 inches) per drop or continuous.
4. Adjustable feeding speed:
0-60mm (0-2.4 inches) /second.
5. Solder feeding method: Single drop, drop by drop or continuity, selected.
6. Soldering iron: 60/150 W. as requested.
7. Heater: 0-600 Degree C. (1110 Degree F.), temperature controlled.
8. Tip Diameter: 6mm (0.24 inches) for 60 W, 10mm (0.4 inches) for 150 W, Any type. Replaceable.
9. Length for cardan arm:
Max 320mm (12.6 inches)
10. Measurement: 150 x 360 x 320mm
(6 x 14.2 x 12.6 inches)
11. Weight: 4.8 kgs (10.5 lbs.)

標準規格及功能

1. 電 源：110/ 220/ 240 V AC., 50/60 HZ，依客戶要求
2. 錫 絲：線徑0.8mm 至1.2mm 皆適用
3. 供錫長度：每次0 - 30mm 可調或連續送錫
4. 供錫速度：每秒0 - 60mm 可調
5. 供錫方式：可任意選擇控制單點、多點或連續供錫
6. 烙 鐵：60W至150W 依客戶需求
7. 電 熱 器：0-600度，溫控
8. 烙 鐵 頭：60W—外徑5.9mm
150W—外徑10mm，式樣可更換
9. 手 臂 長：最長320mm
10. 體 積：150 x 360 x 320 mm
11. 重 量：4.8公斤