

FENG YI STEEL CO., LTD.

Tel:+886-6-5962101 Fax:+886-6-5962102 E-mail: fengyi.ti@msa.hinet.net
 Add: No.11, Ln. 511, Sec. 1, Nan Shiung Rd, Kwan Miao Hsiang, Tainan 71844, Taiwan(R.O.C)

HEX. SOCKET BUTTON HEAD TITANIUM SCREW

※Standard : ISO7380

※Material : Commercially-pure Titanium Grade2

※Chemical composition(wt%) :



N	C	H	Fe	O	Ti
MAX 0.03	MAX 0.08	MAX 0.015	MAX 0.30	MAX 0.25	Bal.

※Screw mechanical properties :

Tensile Strength (MPa)	0.2% Yield Strength(MPa)	Elongation (%)	Hardness (Hv)
400-550	≥ 400	≥ 10	180-250

※Manufacture ability :

Major Dia.	M3	M4	M5	M6	M8	M10
Thread Pitch	0.5	0.7	0.8	1.0	1.25	1.5
Length	8					
	10					
	12					
	16					
	20					
	25					
	30					
	35					
	40					
	45					
	50					
	55					
	60					
	70					
	80					
90						
100						

PS : is able to manufacture size

※**Delivery** : Within 80 days after receipt of 30% down payment.

※**MOQ** : Each size 500pcs.

※**Packing** : Bulk packing.

※**Trade Term** : FOB Kaohsiung(Taiwan).

※**Payment Term** : By T/T at sight.

(30% down payment, 70% against original documents before shipment)

FENG YI STEEL CO., LTD.