


JIS-10K**球墨鑄鐵視窗觀測器
Ductile Iron Sight Glass****螺紋口
Screwed****TH-10K**

TH-10K

標稱壓力 Working pressure marking 10 kgf/cm²
 150°C 以下之靜流水
 Non shock water under 150°C 10 kgf/cm²

測試壓力 Test Pressure


閥體 Body	16 kgf/cm ² (Hydrostatic)
	6 kgf/cm ² (Air)

• Connection Screwed End (P.T)

Size	mm	15	20	25	32	40
	inch	½	¾	1	1¼	1½
L		125	125	125	135	135
H		100	100	100	115	115

Parts and materials list

閥體 Body	FCD450
閥蓋 Cap	FCD450
視窗 Window	High pressure glass
墊片 Gasket	Non Asbestos


JIS-10K**球墨鑄鐵視窗觀測器
Ductile Iron Sight Glass****法蘭口
Flanged****THF-10K**

1/2~2"

標稱壓力 Working pressure marking 10 kgf/cm²
 150°C 以下之靜流水
 Non shock water under 150°C 10 kgf/cm²

測試壓力 Test Pressure

閥體 Body	16 kgf/cm ² (Hydrostatic)
	6 kgf/cm ² (Air)



2½~4"

Parts and materials list

閥體 Body	FCD450
閥蓋 Cap	FCD450
視窗 Window	High pressure glass
墊片 Gasket	Non Asbestos

• Connection Flanged End (R.F)

Size	mm	15	20	25	32	40	50	65	80	100
	inch	½	¾	1	1¼	1½	2	2½	3	4
L		135	135	135	156	156	156	245	245	270
H		95	100	125	135	140	155	220	220	250