



## AC/DC 10~24Watts Wall Mount Series

With safety certificate and meet Energy Star Level V & ErP Stage 2 regulations and RoHS compliance.

### Input

- Input Range 100 to 240 VAC
- Frequency 50 to 60Hz
- Input Current  $\leq 0.6A$
- Inrush Current  $\leq 30A$
- Efficiency 75% Typ.

### Output

- Over Voltage Protection Auto Recovery
- Over Current Protection Auto Recovery
- Short Circuit Protection Auto Recovery

### Environmental

- Operating Temperature 0 to 40°C
- Storage Temperature -20 to 85 °C
- Storage Humidity 5 % to 95%

### Safety

- UL/CUL , FCC,TUV/GS ,CE,CB,PSE, BSMI, KC,EK, CCC, C-Tick, ITACS, BS, PSB EN/IEC 60950



美台日規



歐規



英規



澳規



韓規



巴西



Dimension : 75mm (L)x35mm (W)x55mm (H)

Model No.	Output Power(W)	Output voltage(Vo)	Output Current Max
CF1205	10W	5V	2.0A
CH1212	12W	12V	1.0A
CG1509	15W	9V	1.33A
CH1812	18W	12V	1.5A
CG2412	24W	12V	2.0A
CF2005	24W	5V	4.0A