

CIRCUIT BREAKER

CIRCUIT BREAKER

CBLS Series



3~20Amp 125/250V AC
Mounting Hole: 28.4x13.35mm

88D-15A



15Amp 125V AC
Mounting Hole: 31.2x27mm
Terminal Type: 4.8mm #187

97 Series



1 ~ 15Amp 125/250V AC
Size: 19x11.8x7.4mm
A: PCB Type
B: Solder Type

AR1 Series



5A~50A 125/250VAC 12/24VDC
Size: 32.3x20.6x14.2mm
Pitch Hole: 17.4mm

AR2 Series



5A~50A 125/250VAC 12/24VDC
Mounting Hole: 40mm
Terminal Type: 6.3mm #250

ZE - 800



1.5~20Amp 125/250VAC 32VDC
Mounting Hole: 15.2x13.5mm
UL - 2 ~ 18A 125/250V AC
CSA - 3 ~ 15A 125V AC

88 Series



3~20A 125/250VAC 32VDC
Mounting Hole: Ø11.2x10.0mm

90 Series



1~10Amp 125/250VAC 50VDC
Size: 25.6x8.1x15mm

91 - A Series



1~10Amp 125/250VAC 50VDC
Size: 25.6x8x15.2mm

91 - B Series



1~10Amp 125/250VAC 50VDC
Size: 26x8x17.6mm
Mounting Hole: M8xP0.75

98 Series



3~50Amp 125/250VAC 32VDC
Mounting Hole: Ø15.8x13.8mm
UL, CUL - 3 ~ 30A 125/250V AC
VDE - 3~16A 125/250V AC
TUV, 3C - 3~30A 125/250V AC
31 ~ 50A Non safety

91L Series



5~20Amp 125/250VAC 12V/24VDC
Mounting Hole: M9 - P0.75