## KML-3000-B SERIES LASER LINE PROJECTOR 雷射標線器

:
630 ~ 650 nm (RED)
3 Mw / 5 mW / 10 mW
1 M / 2 M / 3 M
乾電池 LITHIUM CR123 DC3 V (Battery Only)
– 10 ~ 50 °C
Class Ⅲa / Class Ⅲb
> 15,000 小時 (hr)
D 20 × L 96 (mm)
50±5公克(g)(Without Battery)/65±5公克(g)(With Battery)
<ul> <li>焊接加工 Welding process</li> <li>鐵材加工 Metal working</li> <li>木材加工 Wood working</li> <li>布料加工 Fabric processing</li> <li>輸胎成型加工 Tire bonding</li> <li>高爾夫球桿組裝 Golf assembly</li> <li>橡膠加工 Rubber processing</li> <li>印刷品加工 Print processing</li> <li>이유加工 Slitting processing</li> </ul>
<ol> <li>若未使用原廠設計之完整腳座固定雷射頭時,建議使用非金屬材質 (如:塑鋼、電木), 以隔絕雷射頭與機械設備的電位接觸.</li> <li>If you do not use the original design of a complete mounting fixed to the laser head, recommend the use of non-metallic materials (such as: Plastic and bakelite), in order to cut off the laser head and the equipment conductive contact.</li> <li>雷射光對人體眼睛的視網膜會造成傷害,使用操作時請勿直視光源.</li> <li>Do not catch your sight with the beam. It may result in the harm to your eyes.</li> <li>請勿自行調整或拆裝雷射頭上之零件(含螺絲),以避免損壞情況擴大,徒增不必要的維修成本.</li> <li>Please do not adjust the laser head or removable parts (including screws), to avoid damage to expand, and inviting unnecessary maintenance costs.</li> </ol>

## 應用範例 Example:





