

## 規格 SPECIFICATIONS :

波長 Wavelength	630 ~ 650 nm (RED)	
輸出功率 Output Power	3 mW / 5 mW / 8 mW	
標線長度 Line Length	1 M / 2 M / 3 M	
輸入電壓 Input Voltage	AC 90 ~ 260V to DC 5V Adaptor (PS1) or PS3 or PS5	DC 24V
操作溫度 Operating Temp.	- 10 ~ 50 °C	
安全等級 Safety Class	Class IIIa / Class IIIb	
使用壽命 Lifetimes	> 10,000 小時 (hr)	
外觀尺寸 Dimensions	D 15 × L 60 (mm)	D15×L80 (mm)
重量 Weight	20 ± 2 公克 (g)	30 ± 2 公克 (g)
適用行業 Applications	<ul style="list-style-type: none"> <li>● 焊接加工 Welding process</li> <li>● 鐵材加工 Metal working</li> <li>● 木材加工 Wood working</li> <li>● 布料加工 Fabric processing</li> <li>● 輪胎成型加工 Tire bonding</li> <li>● 高爾夫球桿組裝 Golf assembly</li> <li>● 橡膠加工 Rubber processing</li> <li>● 印刷品加工 Print processing</li> <li>● PCB加工 PCB processing</li> <li>● 自行車加工 Bicycle processing</li> <li>● 分條加工 Slitting processing</li> </ul>	
備註 Remarks	<p>1. 若未使用原廠設計之完整腳座固定雷射頭時,建議使用非金屬材質 (如:塑鋼、電木), 以隔絕雷射頭與機械設備的電位接觸。 If you do not use the original design of a complete mounting fixed to the laser head, recommend the use of non-metallic materials (such as: Plastic and bakelite), in order to cut off the laser head and the equipment conductive contact.</p> <p>2. 雷射光對人體眼睛的視網膜會造成傷害,使用操作時請勿直視光源。 Do not catch your sight with the beam. It may result in the harm to your eyes.</p> <p>3. 請勿自行調整或拆裝雷射頭上之零件(含螺絲),以避免損壞情況擴大,徒增不必要的維修成本。 Please do not adjust the laser head or removable parts (including screws), to avoid damage to expand, and inviting unnecessary maintenance costs.</p>	

## 應用範例 Example :

