

**規格 SPECIFICATIONS :**

波 長 Wavelength	630 ~ 650 nm (RED)	
輸出功率 Output Power	1 mW / 3 mW / 5 mW / each line	
標線長度 Line Length	1 M / 2 M / 3 M / each line	
輸入電壓 Input Voltage	AC 90 ~ 260V to DC 5V Adaptor (PS1) or PS3 or PS5	
操作溫度 Operating Temp.	- 10 ~ 50 °C	
安全等級 Safety Class	Class IIIa / Class IIIb	
使用壽命 Lifetimes	20,000 小時 (hr)	
外觀尺寸 Dimensions	D 35 × L 90 (mm)	
重 量 Weight	雷射頭 (Laser Body) 120 ± 10 公克 (g) / 固定座 (Bracket) 280 ± 10 公克 (g)	
適用行業 Applications	<ul style="list-style-type: none"> <li>● 布料加工 Fabric processing</li> <li>● 鐵材加工 Metal working</li> <li>● 裁紙加工 Paper processing</li> </ul>	<ul style="list-style-type: none"> <li>● 縫紉加工 Sewing processing</li> <li>● 自行車加工 Bicycle processing</li> <li>● 印刷品加工 Print processing</li> </ul>
備 註 Remarks	<p>1. 若未使用原廠設計之完整腳座固定雷射頭時,建議使用非金屬材質(如:塑鋼、電木),以隔絕雷射頭與機械設備的電位接觸。 If you do not use the original design of a complete mounting fixed to the laser head, recommend the use of non-metallic materials (such as: Plastic and bakelite), in order to cut off the laser head and the equipment conductive contact.</p> <p>2. 雷射光對人體眼睛的視網膜會造成傷害,使用操作時請勿直視光源。 Do not catch your sight with the beam. It may result in the harm to your eyes.</p> <p>3. 請勿自行調整或拆裝雷射頭上之零件(含螺絲),以避免損壞情況擴大,徒增不必要的維修成本。 Please do not adjust the laser head or removable parts (including screws), to avoid damage to expand, and inviting unnecessary maintenance costs.</p>	

**應用範例 Example :**