

規格 SPECIFICATIONS :

波 長 Wavelength	630 ~ 650 nm (RED)	
輸出功率 Output Power	1 mW	
標線長度 Line Length	1.5 / 3 / 4.5 / 6 / 7.5 / 9 / 10.5 / 12 / 13.5 / 15 cm / each line	
輸入電壓 Input Voltage	AC 90 ~ 260V to DC 5V Adaptor (PS1) or PS3 or PS5	
操作溫度 Operating Temp.	- 10 ~ 50 °C	
安全等級 Safety Class	Class II	
使用壽命 Lifetimes	10,000 小時 (hr)	
外觀尺寸 Dimensions	D 12 × L 53 (mm)	
重 量 Weight	13 ± 2 公克 (g)	
適用行業 Applications	<ul style="list-style-type: none"> ● 布料加工 Fabric processing ● 鐵材加工 Metal working ● 裁紙加工 Paper processing ● 縫紉加工 Sewing processing 	<ul style="list-style-type: none"> ● 自行車加工 Bicycle processing ● 印刷品加工 Print processing ● 高爾夫球具加工 Golf processing
備 註 Remarks	<p>1. 若未使用原廠設計之完整腳座固定雷射頭時,建議使用非金屬材質 (如:塑鋼、電木), 以隔絕雷射頭與機械設備的電位接觸。 If you do not use the original design of a complete mounting fixed to the laser head, recommend the use of non-metallic materials (such as: Plastic and bakelite), in order to cut off the laser head and the equipment conductive contact.</p> <p>2. 雷射光對人體眼睛的視網膜會造成傷害,使用操作時請勿直視光源。 Do not catch your sight with the beam. It may result in the harm to your eyes.</p> <p>3. 請勿自行調整或拆裝雷射頭上之零件(含螺絲),以避免損壞情況擴大,徒增不必要的維修成本。 Please do not adjust the laser head or removable parts (including screws), to avoid damage to expand, and inviting unnecessary maintenance costs.</p>	

應用範例 Example :